Features :

- **Single set point**
- **LED Indications : Relay ON**
- **2 C/O SPDT**

48 x 48mm

Technical specifications

Display	3 digits, 7 segment LED
LED indication	Relay ON
Accuracy	Setting: ± 0.05% of set time or 50msec ; Repeat: ± 0.05%
Start input	Gate/ Pulse (Programmable)
Contact rating	Relay: NO: 10A 250 VAC/ 24 VDC NO/ NC: 5A/ 5A 250 VAC/ 24VDC
Relay contact	2X SPDT
Modes	ON delay, Interval, Cyclic ON first, Cyclic OFF first
Time ranges	0 - 9.99sec, 0 - 99.9sec, 0 - 999sec, 0 - 9:59min: sec, 0 - 99.9min, 0 - 999min, 0 - 9:59hr: min, 0 - 99.9hr, 0 - 999hr
Resolution	0.01sec
Counting direction	Down
Set point	1
Time setting	By keys on front panel
Reset	Front, Remote, On power interruption
Memory	No
Configuration lock	No
Supply voltage	90 to 270 VAC (50/ 60Hz), - 15% to 10% tolerance
Power consumption	4VA max
Temperature	Operating: 0 to 50ºC (32 to 122ºF) Storage: - 20 to 75ºC (- 4 to 167ºF)
Humidity (non - condensing)	95% RH
Mounting	Panel mount
Weight	160 gms

Terminal connections



Dimensions (All are in mm)



DIM	A	B	C	D	E	F	G
XTC543-N	48	48	100	45	7	46	46

Ordering information

XT543-N	90 to 270 VAC/ DC	- - -