

24 x 48mm

Features :

7 ½ digits time/ count totaliser

LCD Hour Meter with Counter

Battery powered


Contact/ Voltage input

Certifications: 


Technical specifications

Display	7½ digits LCD display
Input type	a) 24 to 260 VAC/ DC b) Contact input
Input speed	a) 14Hz b) 100Hz
Accuracy	0.05%
Ranges (For hour meter)	a) 1999.59.59hr: min: sec b) 199999.99hr
Range (For counter)	19999999 counts
Counting direction	Up
Reset	Front, Remote
Supply voltage	Battery powered
Memory retention	Yes
Temperature	Operating: 0 to 50°C Storage: - 20 to 75°C
Humidity (non - condensing)	95% RH
Mounting	Panel mount
Weight	60gms

Terminal connections



Dimensions (All are in mm)



Compliance

Category	Reference Standards	Testing Level
Electrostatic Discharge	IEC 61000-4-2	Level-3
Electrical Fast Transient / Brust	IEC 61000-4-4	Level-3
Electromagnetic Field	IEC 61000-4-3	Level-3
Surge	IEC 61000-4-5	Level-3
Conducted RF	IEC 61000-4-6	Level-2
Rated Power Frequency	IEC 61000-4-8	Level-4

Category	Reference Standards	Testing Level
Voltage Dip / Short Interruptions	IEC 61000-4-11	Level-3
Conducted Emissions	CISPR-11	Class-B
Rated Emissions	CISPR-22	Class-A
Emission & Immunity	IEC 61326-1	
Safety	IEC 61010-1	
PFMF (Passing criteria)	IEC 61000-4-8	Class A

Ordering information

LTC9A	Yes	Yes	CE