96 x 96mm

Features :

- 8 Channels
- On delay/ Interval/ Cyclic ON first/ Cyclic OFF first
- Parallel/ Sequential operation
- Cascade output for channel expansion
- Start, Hold input
- Start delay programmable
- Start, Hold input
- Start delay programmable
- 5 Time ranges
- Memory retention

Technical specifications

Display	4 digits for Timer, 2 digits for channel no.
LED indication	Relay ON, Cascade o/p, Time ranges, ON/ OFF time, Timing in progress
Accuracy	± 0.5% of setting or 50ms, whichever is greater
Start input	Start, Hold
Relay contact	8 nos., NO with single Common
Contact rating	5A @ 230 VAC
Modes	ON delay, Interval, Cyclic ON first, Cyclic OFF first (start up delay & no. of cycles programmable for cyclic mode)
Time ranges	0 - 99.99sec, 0 - 999.9sec, 0 - 99.59min: sec, 0 - 99: 59hr : min, 0 - 999.9hr
Resolution	0.01sec
Counting direction	Up
Set point	8
Time setting	Front keypad
Reset	Front, Remote, Power interruption
Memory retention	Yes
Configuration lock	via rear terminals
No of channels	8 channels
Supply voltage	85 to 270 VAC/ DC (50 or 60 Hz)
Power consumption	3VA Max.
Temperature	Operating: 0 to 50°C Storage: - 5 to 50°C
Humidity (non - condensing)	95% RH
Mounting	Panel mount
Weight	420gms

Terminal connections



Dimensions (All are in mm)



DIM	A	B	C	D	E	F	G
PT380	96	96	70	90	10	92	92

Timing diagrams

1. Function : ON delay



t = set time delay

2. Function : Interval



t = set time delay

3. Function : Cyclic ON First



t1 = ON time ; t2 = OFF time

4. Function : Cyclic OFF First



t1 = OFF time ; t2 = ON time

Ordering information

PT380	85 to 270 VAC/ DC	- - -