55XU

Plug / Panel Mount Timer

48 x 48mm

Features :

- ON delay / Interval
- 12 time ranges
- Universal supply voltage
- LED indications : Power ON, Relay ON
- Compact size

Certifications :

Display specifications

LED indications	Power ON, Relay ON

Input specifications

Accuracy	Setting : ±5% of F.S. Repeat : ±0.5% or 50msec (F.S. = Full scale)

Output specifications

Relay contact	2 C/O SPDT
Contact rating	5A @ 250V AC / 24V DC, Resistive

Functional specifications

Modes	ON delay / Interval
Time ranges	0 - 1sec / min / hr 0 - 3sec / min / hr 0 - 10sec / min / hr 0 - 30sec / min / hr
Resolution	0.1sec
Reset	On interruption of power; Reset time < 100 msec

Auxiliary supply specifications

Supply voltage	20 to 240V AC (50 / 60Hz) 12 to 240V DC
Power consumption	2VA max

Environmental specifications

Temperature	Operating : 0°C to 50°C (32 to 122°F) Storage : -20°C to 75°C (-4 to 167°F)
Humidity (non - condensing)	95% RH

Mechanical specifications

Mounting	Plug / Panel mount
Weight	100 gms

Dimensions



Terminal connections



Timing diagram



Ordering information

Product code	Supply voltage	Certification
55XU-P8-230V-G	20 to 240V AC, 12 to 240V DC	
55XU-T-230V-G	20 to 240V AC, 12 to 240V DC	