

OPERATING INSTRUCTIONS : OP_600SD-CU A5 60GSM PG-2 (OP375-V02)

OP375-V02

SELEC

600SD-2
Operating Instructions

MECHANICAL SPECIFICATIONS

Mounting : Din rail mounting
 Dimension : 17.5 x 90 x 60mm
 Protection Level
 IP 20 for Terminal

WEIGHT
73gms


Please maintain these instructions and review them before using the unit :

Warning :

- The equipment is built-in type with Class II construction and is protected by reinforced insulation.
- The power should be turned off while wiring and maintenance to prevent the risk of electric shock. Do not touch any terminal when the power is ON.
- Wiring shall be done strictly according to the terminal layout with shortest connections.
- Fuse Protection : The equipment does not have Built-in fuse. External fuse of rating 275V DC / 1 A is recommended.


CAUTION :

- This unit is not intended for outdoor use.
- The power connection cable must have a cross-section of at least 1sq.mm and insulation capacity of at least 1.5kV. Use lugged terminals to meet M3screws.
- Clean the equipment with a soft cloth. Do not use any organic solvents like Isopropyl alcohol for cleaning.




17.5mm DIN RAIL

MECHANICAL INSTALLATION




Doc. name : OP INST 600SD-CU OP375-V02(Page 1 of 2) B-B


TERMINAL CONNECTIONS



SCHEMATIC DIAGRAM



RANGE SELECTION



	Run up Time	Pause Time
①	30sec	50ms
②	60sec	50ms
③	60sec	100ms
④	30sec	100ms

MODE OF OPERATION

Supply voltage

Star relay NO contact

Delta relay NO contact

t1 = Run up time, t2 = Pause time

ORDER CODE INFORMATION


Product	Supply	Certification
600SD-2-230	230V AC,	CE
600SD-CU	50 / 60Hz	UL LISTED 45T6 IND. CONT. EQ.
600SD-2-110	110V AC,	CE
600SD-110-CU	50 / 60Hz	UL LISTED 45T6 IND. CONT. EQ.

Note : ■ Applicable

(Specifications subject to change as development is a continuous process.)

PRINCIPLE OF OPERATION

WIRING DIAGRAM



Selec Controls Pvt. Ltd., India

Factory Address :
 EL-27/1, Electronic Zone, TTC Industrial Area,
 MIDC, Mahape, Navi Mumbai - 400 710, INDIA.
 Tel. No. : +91-22-28476443 / 1882
 Fax No. : +91-22-28471733 | Toll free : 1800 227 353
 Website: www.selec.com | Email: sales@selec.com

Doc. name : OP INST 600SD-CU OP375-V02(Page 2 of 2) B-B

OPERATING SIZE : A5 ; PAGE : 1 (B-B)

Prepared By		Checked By		Sales Engg. By		Marking Engg. By		Approval By	
-------------	--	------------	--	----------------	--	------------------	--	-------------	--