## Compliance

Catagony		Standarda compliance	
Category		Standards compliance	
ESD immunity	IEC 61000-4-2	Level III	
Surge immunity	IFC 61000-4-5	+/- 2 kV common mode,	
Curgo minianty	120 0 1000-4-3	+/- 1 kV differential mode	
Dedicted acceptability	150 04000 4 0	Level III, 80 to 1000MHz	
Radiated susceptibility	IEC 61000-4-3	Level II, 1.4GHz to 2GHz Level I, 2GHz to 2.7GHz	
Conducted susceptibility	IEC 61000-4-6	Level II	
Voltage dips and interruptions	IEC 61000-4-11	Dips: 0% residual voltage / 1 cycle (Criteria B), 40% residual voltage / 10 cycles 50Hz / 12 cycles 60Hz (Criteria C)70% residual voltage / 25 cycles50Hz / 30 cycles 60Hz (Criteria C) Interruptions: 0% residual voltage / 250 cycles 50Hz / 300 cycles 60Hz (Criteria C)	
Conducted emission	CISPR-11		
Radiated emission	CISPR-11		
Electrical fast transient	IEC 61000-4-4	Level III	

## Input sensor ranges (For TC / RTD inputs)



## Ordering information



Accessories (Optional)
Standard SELEC accessories that can be used with this product.



Mounting accessories (Supplied with units)