

2 : Output Specification

	50	50	50	50	50	50
	800	800	800	800	1200	1200
	1.5	1.5	1.5	1.5	1.5	1.5
	100	150	100	150	100	150
	0.8	0.9	0.8	0.9	0.8	0.9
	1	1	1	1	1	1

3 : General Specification



	2500 Vrms	4000 Vrms	2500 Vrms	4000 Vrms	2500 Vrms
Ambient Humidity	93% non-condensing				
Heat sink Thermal Resistance:	1°C/W				

4 : Housing Specification



Weight	87.2 g approx
Baseplate	
Material	Glass filled polyester
LED input Status Indicator	Red

5 : Circuit Block Diagram


RSS Series



6 : Surge Current Information




7 : Thermal Derating Curves




Ambient temperature [°C]
Note.: Heat sink used with a radiation efficiency of 1°C/W

8 : Wiring



9 : Dimension (mm)



10 : Tightening Torque

Screw Size	Wire Size (Solid)	Tightening Torque
M4 Screws (control input)	18..14 AWG (0.75..2.5 mm ²) 2 x 18..14 AWG (0.75..2.5 mm ²)	1.2 N-m
M5 Screws (load output)	16..8 AWG (1.5..10 mm ²) 2 x 16..8 AWG (1.5..10 mm ²)	2.0 N-m