

)HDWXUHV

MXLDW LQ 5+ FDEOH

8LQJOH SKDVH 3KDVH &7

ARQYHUWHU IRUFEXUUHQW PHDVXUHPHQW


&HWL CE DFLRQ

&7 3+ ' PP \$ *

6SHFLILFDWLRQ




'LPHQVLRQ \$OO DUH LQ PP




&7 3+ [PP \$ *

6SHFLILFDWLRQ



'LPHQVLRQ \$OO DUH LQ PP




&7 3+ ' PP \$ *

6SHFLILFDWLRQ



'LPHQVLRQ \$OO DUH LQ PP




&7 3+ [PP \$ *

6SHFLILFDWLRQ




'LPHQVLRQ \$OO DUH LQ PP




Mounting	Panel mount
Bezel size	72mm x 72mm
Overall depth	50mm
Weight	206gm
Torque at terminals	0.68 N-m to 0.79 N-m
Wire gauge at terminals	20 to 14 AWG; 75°C
Mounting position	Vertical

Terminal connections



Dimensions (All are in mm)



Standards compliance

Category	Standards	Compliance
ESD Immunity	IEC 61000 - 4 - 2	Level IV (Air discharge : 8kV), (Contact discharge : 4kV)
Surge immunity	IEC 61000 - 4 - 5	+ / - 2kV Common mode, (Line to ground)
Radiated susceptibility	IEC 61000 - 4 - 3	Level III, 80 to 1000MHz (10V / m) Level II, 1.4GHz to 2GHz (3V / m) Level I, 2GHz to 2.7GHz (1V / m)
Conducted susceptibility	IEC 61000 - 4 - 6	Level II (3V / m)
Voltage dips and interruptions	IEC 61000 - 4 - 11	Dips : 0% Residual voltage / 1 Cycle (Criteria B), 40% Residual voltage / 10 Cycles 50Hz / 12 Cycles 60Hz (Criteria C), 70% Residual voltage / 25 cycles 50Hz / 30 Cycles 60Hz (Criteria C) Interruptions : 0% Residual voltage / 250 Cycles 50Hz / 300 Cycles 60Hz (Criteria C)
Conducted emission	CISPR - 11	
Radiated emission	CISPR - 11	
Electrical fast transient	IEC 61000 - 4 - 4	Level III (2kV)

Ordering information

MV2307-230V-CE	240V AC ±20%	CE
MV2307-110V-CE	110V AC, ±20%	CE  LISTED