


Cyclic Timer With Unequal On-Off Time, 6 Time Range



Operating Instruction

TABLE OF CONTENT

1. MANUAL OVERVIEW.	Page No.03
2. SAFETY RECOMMENDATIONS	Page No.04
• Caution	
• Wiring guidelines	
3. SPECIFICATION	Page No.05
• Technical specification	
4. INSTALLATION	Page No.06
• Panel dimensions	
• Front plate description	
• Terminal connection	
• Product data	
• Terminal description	



DIN 22.5mm

Salient features

- Cyclic timer with unequal ON & OFF time
- 6 Time ranges
- Universal supply voltage
- LED Indications: Power ON, Relay ON
- Finger safe terminals

Ordering information

Product code	Supply voltage	Certification
800XC	20 to 240V AC, 12 to 240V DC	---

Caution

- This unit is not intended for outdoor use.
- The power connection cable must have a cross-section of at least 1sq.mm and insulation capacity of at least 1.5kV. Use lugged terminals to meet M3 screws.
- The output connections must not be loaded beyond the specified values/range.
- Avoid inflow of dust and contact of conductive material with the internal circuitry of the unit.
- Clean the equipment with a clean, soft cloth. Do not use any organic solvents.

Wiring guidelines


1. The Equipment is built-in type with class II construction and is protected by Reinforced Insulation. Terminals are a part of the front panel and are protected by means of finger guards. by Reinforced Insulation. Terminals are a part of the front panel and are protected by means of finger guards. Finger guards are not to be removed during wiring, installation, operation or maintenance.
2. The power should be turned off while wiring and maintenance to prevent the risk of electric shock. Do not touch any terminals when the power is ON.
3. Wiring shall be done strictly according to the terminal layout with shortest connections.
4. Fuse Protection: The equipment does not have Built-in fuse. External fuse of rating 275 VDC/1 A is recommended.

SPECIFICATION


Technical specifications	
Time setting range	0-1 Sec/Min/Hrs (ON Time & OFF Time User selectable via Dip Switches)
Supply voltage	20V to 240V AC (50/60Hz) 12V to 240V DC
Delay modes	Cyclic ON first or OFF first
Contact type	DPDT (2C/O)
Contact capacity	250VAC, or 24VDC 5A resistive load
Electrical life of relay	100,000 operations
Mechanical life of relay	10,00,000 operations
Accuracy setting	±5% of full scale
Repeat	±0.5% of full scale
LED indication	Power 'ON', Relay 'ON'
Reset	On interruption of Power Reset time less than 100ms
Weight	115 gm
Connecting capacity	Rigid 1x4mm - 2x2.5mm
Flexible with ferrules	1x2.5mm - 2x1.5mm
Tightening torque	0.5 to 0.8 Nm
Size (in mm)	22.5(W) x 72.25(H) x 90(D)
Temperature	Operating: 0 °C to 50 °C Storage: -20 °C to 75 °C
Humidity	Up to 95%RH
Mounting	DIN rail / Wall mounting
Pollution degree	2

INSTALLATION


Panel dimensions



Front plate description




Terminal connections




Typical load connection


1. For load current less than 0.5A




2. For bigger loads, use interposing relay/contactors



Product data



DIP Switch setting



Terminal description

Terminal	Description
A1	LINE
A2	NEUTRAL
15	RELAY COM1
16	RELAY NC1
18	RELAY NO1
25	RELAY COM2
26	RELAY NC2
28	RELAY NO2

Head Office :

Selec Controls Pvt. Ltd.

EL-27/1, Electronic Zone, TTC Industrial Area, MIDC, Mahape, Navi Mumbai 400710, India.

Website : www.selec.com

For Sales & Support,

Mobile No. : +91-9136977315, **Email :** sales@selec.com

For Service,

Tel. No. : +91-7498077172 / +91-7400069545, **Email :** service@selec.com

Selec USA : www.selec.com/us/en | **Selec GmbH :** www.selec-europe.com | **Selec Australia :** www.selec.com/au/en
