55MF-P

Plug Mount Timer

Preliminary Datasheet

Features :

- ! 10 Functions
- ! 25 Time Ranges
- ! Universal Supply Voltage
- ! nobs for mode setting, Time range, Time scale & division
- ! LED Indications : Power ON, Relay ON

Certifications : CE

4 x 4 mm

Display Specifications

LED Indications	Power ON, Relay ON

Input Specifications

Accuracy Setting	±5% of F.S. or 50msec (Whichever is greater)
Repeat	±0.5% or 50msec (Whichever is greater)

Output Specifications

Relay contact	2 1 C/O SPDT
Contact rating	6A 250AC / 24V DC, resistive

Functional Specification

Modes	On Delay, Pulse Output with instantaneous limit, ON Delay with Instantaneous limit, Interval with Instantaneous limit, Cyclic Equal OFF First, Cyclic Equal OFF First with Instantaneous limit, Cyclic Equal ON First, Cyclic Equal ON First with Instantaneous limit, Star delta with 50ms pause time, Star delta with 100ms pause time
Resolution	0.05sec
Reset	On power interruption, Reset time < 100msec

Time Specification

Time range	Time unit	Time setting range
0.5	S	0.05 to 0.5 sec
1		0.1 to 1 sec
3		0.3 to 3 sec
5		0.5 to 5 sec
10		1 to 10 sec
0.5	M	0.05 to 0.5 min
1		0.1 to 1 min
3		0.3 to 3 min
5		0.5 to 5 min
10		1 to 10 min
0.5	H	0.05 to 0.5 hour
1		0.1 to 1 hour
3		0.3 to 3 hour
5		0.5 to 5hour
10		1 to 10 hour
0.5	10H	0.5 to 5 hour
1		1 to 10 hour
3		3 to 30 hour
5		5 to 50 hour
10		10 to 100 hour
0.5	30H	1.5 to 15 hour
1		3 to 30 hour
3		9 to 90 hour
5		15 to 150 hour
10		30 to 300 hour

Note : Time range x Time unit = Maximum time setting range

Auxiliary Supply Specifications

Supply voltage	20-240V AC / DC (50 / 60Hz)
Power consumption	5VA max

Environmental Specification

Temperature	Operating : 0 to 50 C (32 to 122oF) Storage : -20 to 75 C (-4 to 167oF)
Humidity (non - condensing)	95% RH

Mechanical Specifications

Mounting	Plug mount
Weight	100gms

Dimensions All are in mm



Terminal connections



Pin Soc et

Timing Diagram

A ON Delay



B Pulse Output with instantaneous limit



The pulse output is 500msec fixed.

C ON Delay with Instantaneous limit



D Interval with Instantaneous limit



E Cyclic E ual OFF First



F Cyclic E ual OFF First with Instantaneous limit



Cyclic E ual ON First



H Cyclic E ual ON First with Instantaneous limit



I Star delta with 50ms pause time



Star delta with 100ms pause time



Ordering Information

Product Code	Supply Voltage	Certification
55MF-P8	20-240V AC / DC, 50/60Hz	CE