



FRONT PANEL DESCRIPTION




1. Red LED indicates Relay R1 & Green LED indicates Relay R2
2. Knob for Operating mode Selection
3. Red LED indicates Power ON
4. Knob for time selection
(The marking 1 to 10 represents timing in proportion to full scale time range)
5. Knob for time range selection
6. Knob for time scale selection

FUNCTIONS


A | Signal ON Delay




B | Interval




C | Cyclic Equal Off First




D | Cyclic Equal On First




E | Signal OFF Delay




F | Signal ON/OFF Delay




G | Interval After Break




H | Single Shot



I | Retriggerable Single Shot



J | Delay On Make/Break



Note :

1. If START terminal is closed, time cycle (t) will start.
2. If timer is cut or RESET terminal is closed, the timer will be reset.
3. If INHIBIT terminal is closed during a time-cycle, the time will be stopped until INHIBIT terminal is opened.
4. When using mode C and D, setting a very small time may not guarantee proper operation.
Set time more than 100ms.

t: Set Time, t=t1+t2, t>t-a

ORDER CODE INFORMATION

Product	Supply	Certification
55MF-P11	20-240 VAC/DC 50/60Hz	CE

(Specifications are subject to change, since development is a continuous process.)

Selec Controls Pvt. Ltd., India

Factory Address :

EL-27/1, Electronic Zone, TTC Industrial Area,
MDC, Mahape, Navi Mumbai - 400 710, INDIA.
Tel. No. : +91-22-28476443 / 1882
Fax No. : +91-22-28471733 | Toll free : 1800 227 353
Website: www.selec.com | Email: sales@selec.com