

| | |
|---|---|
| Temperature | Operating: -10º to +55ºC<br>Storage: -20º to +75ºC |
| Humidity (Non-condensing) | Upto 85% RH |

| | |
|---|---|
| Mounting | Panel mount |
| Weight | 357gm |

## Terminal connections




## Dimensions (All are in mm)




## Standards compliance

| Category | Standards | Compliance |
|---|---|---|
| ESD Immunity | IEC 61000 - 4 - 2 | Level IV (Air discharge : 8kV), (Contact discharge : 4kV) |
| Surge immunity | IEC 61000 - 4 - 5 | + / - 2kV Common mode, (Line to ground) |
| Radiated susceptibility | IEC 61000 - 4 - 3 | Level III, 80 to 1000MHz (10V / m)<br>Level II, 1.4GHz to 2GHz (3V / m)<br>Level I, 2GHz to 2.7GHz (1V / m) |
| Conducted susceptibility | IEC 61000 - 4 - 6 | Level II (3V / m) |
| Voltage dips and interruptions | IEC 61000 - 4 - 11 | **Dips :** 0% Residual voltage / 1 Cycle (Criteria B), 40% Residual voltage / 10 Cycles 50Hz / 12 Cycles 60Hz (Criteria C), 70% Residual voltage / 25 cycles 50Hz / 30 Cycles 60Hz (Criteria C)<br>**Interruptions :** 0% Residual voltage / 250 Cycles 50Hz / 300 Cycles 60Hz(Criteria C) |
| Conducted emission | CISPR - 11 | |
| Radiated emission | CISPR - 11 | |
| Electrical fast transient | IEC 61000 - 4 - 4 | Level III (2kV) |

## Ordering information

| | | |
|---|---|---|
| **VAF36A-230V-CE** | 230V AC | CE |
| **VAF36A-110V-CU** | 110V AC | c UL us LISTED |